

# SLP Stage Notes

## SLP15 Notes

- Note 1: Acceleration Force given is based on the output with the use of the following driver - SLP15: (14) Hitachi Production Machine System ADA3-01LL2
- Note 2: The effective amperage when the temperature increase of the coil front becomes 110K
- Note 3: An average value of U-V, U-W, and V-W
- Note 4: There are instances when this is not achieved due to load or operation specifications
- Note 5: There are instances when this is not achieved due to the length of the stroke
- Note 6: Contact NPA for longer stroke lengths

## SLP25 Notes

- Note 1: Acceleration Force given is based on the output with the use of the following driver - SLP25: (14) Hitachi Production Machine System ADA3-01LL2
- Note 2: The effective amperage when the temperature increase of the coil front becomes 110K
- Note 3: An average value of U-V, U-W, and V-W
- Note 4: There are instances when this is not achieved due to load or operation specifications
- Note 5: There are instances when this is not achieved due to the length of the stroke
- Note 6: Contact NPA for longer stroke lengths

## SLP35 Notes

- Note 1: Acceleration Force given is based on the output with the use of the following driver - SLP35: (14) Hitachi Production Machine System ADA3-01LL2
- Note 2: The effective amperage when the temperature increase of the coil front becomes 110K.
- Note 3: An average value of U-V, U-W, and V-W.
- Note 4: There are instances when this is not achieved due to load or operation specifications.
- Note 5: There are instances when this is not achieved due to the length of the stroke.
- Note 6: Contact NPA for longer stroke lengths.